ONLINE CERTIFICATIONS DIRECTORY

VIZM.EX6464
Fittings, Rubber Gasketed

Page Bottom

Fittings, Rubber Gasketed

See General Information for Fittings, Rubber Gasketed

JINAN MEIDE CASTING CO LTD EX6464
3 NANMEN RD
PINGYIN
JINAN, SHANDONG 250400 CHINA

Coupling

Model	Groove Type	Pipe	Size (in.)	Rated Pressure (psig)
1G	Rolled	10	1-1/4, 1-1/2, 2-1/2	500
1G	Rolled	10	2, 3, 4, 5, 6	300
1G	Rolled	10	8	450
1G	Rolled	10	10, 12	300
1G	Rolled	1387-10	3 OD, 6-1/2 OD	300
1G	Rolled	1387-M	5-1/2 OD	450
1G	Rolled, Cut	40	1-1/4, 1-1/2	500
1G	Rolled, Cut	40	2, 2-1/2, 3, 4, 5, 6	300
1G	Rolled, Cut	40	8	450
1G	Rolled, Cut	40	10, 12	300
1G	Rolled, Cut	1387-40	3 OD, 6-1/2 OD	300
1G	Rolled, Cut	1387-H	5-1/2 OD	450
1G	Rolled, Cut	4200	33.7 / 3.2mm, 108.0 / 4.0mm	500
1G	Rolled, Cut	4200	133.0 / 5.4mm, 159.0 / 4.0mm	300
1G	Rolled, Cut	3454-20	267.4 / 6.4mm, 318.5 / 6.4mm	225
1G	Rolled, Cut	4200	355.6 / 6.3mm, 406.4 / 6.3mm	175
1GS	Rolled	10	4	365
1GS	Rolled	10	3, 6, 8	300
1GS	Rolled	40	3, 4, 6, 8	300
1GS	Rolled	1387-M	3 OD, 5-1/2 OD, 6-1/2 OD	300
1GS	Rolled	1387-H	3 OD, 5-1/2 OD, 6-1/2 OD	300
1GS	Rolled, Cut	4200	108.0 / 4.0mm, 141.3 / 6.3mm, 159.0 / 4.0mm	300
1GS	Rolled, Cut	3454-20	216.3 / 6.4mm	300
1GK	Rolled, Cut	4200 E	1-1/4, 1-1/2, 2	500
1GK	Rolled, Cut	4200 E	3, 4	300
1GK	Rolled, Cut	4200 E	76.1mm	300
1GK	Rolled, Cut	4200 D	139.7mm	300
1GK	Rolled, Cut	1387-M	165.1mm	300
1GK	Rolled, Cut	3454-20	216.3mm	300
R10	Rolled, Cut	3452-SPP SGP	2, 76.1mm, 3, 4, 139.7mm, 165.1mm, 216.3mm, 267.4mm, 318.5mm	300

R20	Rolled, Cut	3454-40	2, 76.1mm, 3, 4, 139.7mm, 165.1mm, 216.3mm, 267.4mm, 318.5mm	500

Flexible coupling

Model	Groove Type	Pipe	Size (in.)	Rated Pressure (psig)
1N	Rolled	10	1-1/4, 1-1/2, 2, 2-1/2, 3, 4, 5, 6	300
1N	Rolled	10	8	450
1N	Rolled	1387-10	3 OD, 6-1/2 OD	300
1N	Rolled	1387-M	5-1/2 OD	450
1N	Rolled	1387-M, 10	2-1/2 x 2; 3 OD x 1-1/2, 2; 3 x 2, 2-1/2, 3 OD; 4 x 2, 2-1/2, 3 OD, 3; 6-1/2 OD x 4; 6 x 4; 8 x 6-1/2 OD, 6	300
1N	Rolled, Cut	40	1-1/4, 1-1/2, 2, 2-1/2, 3, 4, 5, 6	300
1N	Rolled, Cut	40	8	450
1N	Rolled, Cut	1387-40	3 OD, 6-1/2 OD	300
1N	Rolled, Cut	1387-H	5-1/2 OD	450
1N	Rolled, Cut	1387-H, 40	2-1/2 x 2; 3 OD x 1-1/2, 2; 3 x 2, 2-1/2, 3 OD; 4 x 2, 2-1/2, 3 OD, 3; 6-1/2 OD x 4; 6 x 4; 8 x 6-1/2 OD, 6	300
1N	Rolled, Cut	4200	33.7 / 3.2mm, 108.0 / 4.0mm	500
1N	Rolled, Cut	4200	133.0 / 5.4mm, 159.0 / 4.0mm	300
1N	Rolled, Cut	4200	60.3 / 3.2 x 48.3 / 4.0mm; 73.0 / 3.2 x 33.7 / 3.2mm; 76.1 / 3.6 x 33.7 / 3.2mm; 88.9 / 3.2 x 33.7 / 3.2mm; 114.3 / 3.6 x 33.7 / 3.2mm; 168.3 / 4.0 x 88.9 / 3.2mm	300
1N	Rolled, Cut	4200	273.0 / 6.3mm, 323.9 / 6.3mm	225
F1	Rolled, Cut	3452-SPP SGP	216.3mm, 267.4mm, 318.5mm	300
1NH	Rolled, Cut	4200	60.3 / 3.2mm, 73.0 / 3.2mm, 76.1 / 3.6mm, 88.9 / 3.2mm, 114.3 / 3.6mm, 141.3 / 6.3mm	500
1NH	Rolled, Cut	4200	168.3 / 4.0mm, 219.1 / 5.0mm	300
1NH	Rolled, Cut	1387 M	165.1 / 5.0mm	300

Flange adapter

Model	Groove Type	Pipe	Size (in.)	Rated Pressure (psig)
321	Rolled	10	2, 2-1/2, 3, 4, 5, 6, 8	300
321	Rolled	1387-10	3OD, 6-1/2 OD	300
321	Rolled	10	10, 12	225
321	Rolled, Cut	40	2, 2-1/2, 3, 4, 5, 6, 8	300
321	Rolled, Cut	1387-40	3OD, 6-1/2 OD	300
321	Rolled, Cut	40	10, 12	225

321	Rolled, Cut	4200	48.3 / 4.0mm, 108.0 / 3.6mm	300
321	Rolled, Cut	4200	133.0 / 3.2mm, 139.7 / 3.6mm, 159.0 / 4.5mm	225
321A	Rolled	10	2, 2-1/2, 3, 4	300
321A	Rolled, Cut	4200	219.1 / 5.0mm, 273.0 / 6.3mm, 323.9 / 6.3mm	175
321AS	Rolled	10	2, 2-1/2, 3	300
321AS	Rolled	10	4, 5	225
321H	Rolled, Cut	1387-M	165.1mm	225
321HS	Rolled, Cut	4200	108.0 / 3.6mm	365
321HS	Rolled, Cut	1387-M	165.1mm	225
321S	Rolled	10	1-1/2, 2, 3, 4	300
321S	Rolled	10	6	225
321S	Rolled, Cut	4200	76.1 / 2.9mm, 108.0 / 3.6mm, 133.0 / 3.2mm	300
321S	Rolled, Cut	4200	139.7 / 3.6mm, 159.0 / 4.5mm	225
321S	Rolled, Cut	1387-M	165.1mm	225

Side outlet

Model	Outlet Type	Pipe	Size (in.)	Rated Pressure (psig)
3G	Grooved	10, 40	2 x 1-1/4, 1-1/2;	300
			2-1/2 x 1-1/4, 1-1/2;	
			3 x 1-1/4, 1-1/2, 2;	
			4 x 1-1/4, 1-1/2, 2, 2-1/2, 3;	
			5 x 1-1/4, 1-1/2, 2, 2-1/2, 3;	
			6 x 1-1/4, 1-1/2, 2, 2-1/2, 3, 4	
3G	Grooved	1387-M, 1387-H	3 OD x 1-1/4, 1-1/2;	300
			5-1/2 OD x 2, 2-1/2, 3;	
			6-1/2 OD x 2, 2-1/2, 3	
3G	Grooved	10	3 x 1;	300
			4 x 1;	
			8 x 2, 2-1/2, 76.1mm, 3, 108.0mm, 4	
3G	Grooved	4200	76.1 / 3.6 x 33.7 / 3.2mm;	300
			133.0 / 3.2mm x 88.9mm;	
			139.7 / 3.6mm x 42.4mm, 48.3mm;	
			273.0 / 6.3 x 108.0 / 4.0mm, 114.3 / 3.6mm	
3G	Grooved	4200	139.7 / 3.6mm x 114.3mm;	175
			159.0 / 4.5mm x 108.0mm, 114.3mm	
3G	Grooved	1387-M	165.1 x 114.3mm	225
3GS	Grooved	10	3 x 1, 1-1/4, 1-1/2, 2;	300
			4 x 1, 1-1/4, 1-1/2, 2, 2-1/2, 76.1mm, 3;	
			6 x 1-1/4, 1-1/2, 2, 2-1/2, 76.1mm, 3;	
			8 x 2, 2-1/2, 76.1mm, 3, 108.0mm, 4	
3GS	Grooved	10	6 x 4	225
3GS	Grooved	4200	133.0 / 3.2mm x 88.9mm;	300
			139.7 / 3.6mm x 42.4mm, 48.3mm, 60.3mm, 76.1mm, 88.9mm	
3GS	Grooved	4200	139.7 / 3.6mm x 114.3mm;	175
			159.0 / 4.5mm x 108.0mm, 114.3mm	

3GS	Grooved	1387-M	165.1 x 42.4mm, 48.3mm, 60.3mm, 76.1mm, 88.9mm	300
3GS	Grooved	1387-M	165.1 x 108.0mm, 114.3mm	225
3J	Threaded	10, 40	2 x 1, 1-1/4, 1-1/2;	300
			2-1/2 x 1, 1-1/4, 1-1/2;	
			3 x 1, 1-1/4, 1-1/2, 2;	
			4 x 1, 1-1/4, 1-1/2, 2, 2-1/2, 3;	
			5 x 1-1/4, 1-1/2, 2, 2-1/2, 3;	
			6 x 1-1/4, 1-1/2, 2, 2-1/2, 3, 4	
3J	Threaded	1387-M, 1387-H	3 OD x 1, 1-1/4, 1-1/2;	300
			5-1/2 OD x 1, 1-1/4, 1-1/2, 2, 2-1/2, 3;	
			6-1/2 OD x 1, 1-1/4, 1-1/2, 2, 2-1/2, 3	
3J	Threaded	10	3 x 1/2, 3/4;	300
			4 x 1/2, 3/4;	
			8 x 1, 1-1/4, 1-1/2, 2, 2-1/2, 76.1mm, 3, 4	
3J	Threaded	4200	273.0 / 6.3 x 114.3 / 3.6mm	225
3J	Threaded	4200	139.7 / 3.6mm x 114.3mm;	175
			159.0 / 4.5mm x 114.3mm	
3J	Threaded	4200	60.3 / 3.2 x 21.3 / 2.8mm, 26.9 / 2.9mm;	300
			73.0 / 3.2 x 21.3 / 2.8mm, 26.9 / 2.9mm;	
			76.1 / 3.6 x 21.3 / 2.8mm, 26.9 / 2.9mm;	
			108.0 / 3.6mm x 21.3mm, 26.9mm, 33.7mm, 42.4mm, 48.3mm, 60.3mm, 76.1mm;	
			133.0 / 3.2mm x 21.3mm, 26.9mm, 33.7mm, 42.4mm, 48.3mm, 60.3mm, 76.1mm, 88.9mm;	
			139.7 / 3.6mm x 21.3mm, 26.9mm;	
			159.0 / 4.5mm x 21.3mm, 26.9mm, 33.7mm, 42.4mm, 48.3mm, 60.3mm, 76.1mm, 88.9mm;	
			273.0 x 48.3 / 4.0mm, 60.3 / 3.2mm, 76.1 / 3.6mm, 88.9 / 3.2mm	
3J	Threaded	1387-M	165.1 x 21.3mm, 26.9mm	300
3J	Threaded	1387-M	165.1 x 114.3mm	225
3JS	Threaded	10	3 x 1/2, 3/4, 1, 1-1/4, 1-1/2, 2;	300
			4 x 1/2, 3/4, 1, 1-1/4, 1-1/2, 2, 2-1/2, 76.1mm, 3;	
			6 x 1, 1-1/4, 1-1/2, 2, 2-1/2, 76.1mm, 3;	
			8 x 1, 1-1/4, 1-1/2, 2, 2-1/2, 76.1mm, 3, 4	
3JS	Threaded	10	6 x 4	225
3JS	Threaded	4200	108.0 / 3.6mm x 21.3mm, 26.9mm, 33.7mm, 42.4mm, 48.3mm, 60.3mm, 76.1mm;	300
			133.0 / 3.2mm x 21.3mm, 26.9mm, 33.7mm, 42.4mm, 48.3mm, 60.3mm, 76.1mm, 88.9mm;	
			139.7 / 3.6mm x 21.3mm, 26.9mm, 33.7mm, 42.4mm, 48.3mm, 60.3mm, 76.1mm, 88.9mm;	
			159.0 / 4.5mm x 21.3mm, 26.9mm, 33.7mm, 42.4mm, 48.3mm, 60.3mm, 76.1mm, 88.9mm	
3JS	Threaded	4200	139.7 / 3.6mm x 114.3mm;	175
			159.0 / 4.5mm x 114.3mm	
3JS	Threaded	1387-M	165.1 x 21.3mm, 26.9mm, 33.7mm, 42.4mm, 48.3mm, 60.3mm, 76.1mm, 88.9mm	300
3JS	Threaded	1387-M	165.1 x 114.3mm	225
3L	Threaded	4200	42.4 / 3.6 x 21.3 / 2.8mm, 26.9 / 2.9mm, 33.7 / 3.2mm;	300

			48.3 / 4.0 x 21.3 / 2.8mm, 26.9 / 2.9mm, 33.7 / 3.2mm;	
			60.3 / 3.2 x 21.3 / 2.8mm, 26.9 / 2.9mm, 33.7 / 3.2mm;	
			73.0 / 3.2 x 21.3 / 2.8mm, 26.9 / 2.9mm, 33.7 / 3.2mm;	
			76.1 / 3.6 x 21.3 / 2.8mm, 26.9 / 2.9mm, 33.7 / 3.2mm;	
			88.9 / 3.2 x 33.7 / 3.2mm	
4G	Grooved	10, 40	2 x 1-1/4, 1-1/2;	300
			2-1/2 x 1-1/4, 1-1/2;	
			3 x 1-1/4, 1-1/2, 2;	
			4 x 1-1/4, 1-1/2, 2, 2-1/2, 3;	
			5 x 1-1/4, 1-1/2, 2, 2-1/2, 3;	
			6 x 1-1/4, 1-1/2, 2, 2-1/2, 3, 4	
4G	Grooved	1387-M, 1387-H	3 OD x 1-1/4, 1-1/2;	300
			5-1/2 OD x 2, 2-1/2, 3;	
			6-1/2 OD x 2, 2-1/2, 3	
4J	Threaded	10, 40	2 x 1, 1-1/4, 1-1/2;	300
			2-1/2 x 1, 1-1/4, 1-1/2;	
			3 x 1, 1-1/4, 1-1/2, 2;	
			4 x 1, 1-1/4, 1-1/2, 2, 2-1/2, 3;	
			5 x 1-1/4, 1-1/2, 2, 2-1/2, 3;	
			6 x 1-1/4, 1-1/2, 2, 2-1/2, 3, 4	
4J	Threaded	1387-M, 1387-H	3 OD x 1, 1-1/4, 1-1/2;	300
			5-1/2 OD x 1, 1-1/4, 1-1/2, 2, 2-1/2, 3;	
			6-1/2 OD x 1, 1-1/4, 1-1/2, 2, 2-1/2, 3	
4JG	Threaded and Grooved	10, 40	2 x 1-1/4, 1-1/2;	300
			2-1/2 x 1-1/4, 1-1/2;	
			3 x 1-1/4, 1-1/2, 2;	
			4 x 1-1/4, 1-1/2, 2, 2-1/2, 3;	
			5 x 1-1/4, 1-1/2, 2, 2-1/2, 3;	
			6 x 1-1/4, 1-1/2, 2, 2-1/2, 3, 4	
4JG	Threaded and Grooved	1387-M, 1387-H	3 OD x 1-1/4, 1-1/2;	300
			5-1/2 OD x 2, 2-1/2, 3;	
			6-1/2 OD x 2, 2-1/2, 3	

The fittings are suitable for use in dry pipe systems for temperatures to -40 F with the exception of Model 1GK.

Model 3J, 3JS and 3L in the 1/2 in. and 3/4 in. nominal outlet sizes are intended for direct connection to sprinklers.

Models 3J, 3JS and 4J in the 1 in. nominal outlet sizes are intended for direct connection to sprinklers.

Models 3G, 3GS, 3J, 3JS, 3L, 4G, 4J and 4JG in the 1 in. and larger nominal outlet sizes are intended for connection to system piping.

10 refers to Schedule 10 steel pipe in accordance with NFPA 13.

40 refers to Schedule 40 steel pipe in accordance with NFPA 13.

1387-10 refers to BS 1387 Schedule 10 steel pipe

1387-40 refers to BS 1387 Schedule 40 steel pipe

1387-M refers to BS 1387 medium steel pipe

1387-H refers to BS 1387 heavy steel pipe

4200 refers to ISO 4200 Group 1 steel pipe

4200 D refers to ISO 4200 Group 1 Type D steel pipe

4200 E refers to ISO 4200 Group 1 Type E steel pipe

3454-20 refers to JIS G3454 Schedule 20 steel pipe

3452-SPP SGP refers to JIS G3452 steel pipe.

3454-40 refers to JIS G3452 Schedule 40 steel pipe.

Trademark and/or Tradename:

Last Updated on 2014-11-03

Questions? Print this page Terms of Use Page Top

© 2016 UL LLC

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2016 UL LLC".