



**HHXX.EX6624**  
**Fittings, Cast Iron, Ductile Iron, Malleable Iron and Bronze**

Page Bottom

**Fittings, Cast Iron, Ductile Iron, Malleable Iron and Bronze**

See General Information for Fittings, Cast Iron, Ductile Iron, Malleable Iron and Bronze

**JINAN MEIDE CASTING CO LTD**  
 3 NANMEN RD  
 PINGYIN  
 JINAN, SHANDONG 250400 CHINA

EX6624

**Ductile Iron Fittings (ANSI/ASME B16.3)**

**Fittings fabricated with dimensional specifications in accordance with ANSI/ASME B16.3**

Model	Configuration	Size, in.	Rated Pressure, psig
90	90° Elbow	1/2, 3/4, 1,	500
		1-1/4, 1-1/2, 2, 2-1/2,	
		3, 4	
90R	Reducing 90° Elbow	3/4 x 1/2	500
		1 x 1/2, 3/4	
		1-1/4 x 1/2, 3/4, 1	
		1-1/2 x 1/2, 3/4, 1, 1-1/4;	
		2 x 1/2, 3/4, 1, 1-1/4, 1-1/2	
		2-1/2 x 1-1/2, 2	
		3 x 3/4	
120	45° Elbow	1/2, 3/4, 1,	500
		1-1/4, 1-1/2, 2, 2-1/2	
130	Tee	1/2, 3/4, 1,	500
		1-1/4, 1-1/2, 2, 2-1/2,	
		3, 4	
130R	Reducing Tee	3/4 x 3/4 x 1/2, 1	500
		3/4 x 1/2 x 1/2, 3/4	
		1 x 1/2 x 1	
		1 x 3/4 x 3/4, 1	
		1 x 1 x 1/2, 3/4, 1-1/4, 1-1/2	
		1-1/4 x 1/2 x 1-1/4	
		1-1/4 x 3/4 x 1-1/4	
		1-1/4 x 1 x 1/2, 3/4, 1, 1-1/2, 1-1/4	
		1-1/4 x 1-1/4 x 1/2, 3/4, 1, 1-1/2, 2	

		1-1/2 x 1/2 x 1-1/4, 1-1/2	
		1-1/2 x 3/4 x 1-1/4, 1-1/2	
		1-1/2 x 1 x 1/2, 3/4, 1, 1-1/4, 1-1/2	
		1-1/2 x 1-1/4 x 1/2, 3/4, 1, 1-1/4, 1-1/2, 1, 2	
		1-1/2 x 1-1/2 x 1/2, 3/4, 1, 1-1/4, 2	
		2 x 1 x 2	
		2 x 1-1/4 x 2	
		2 x 1-1/2 x 1/2, 3/4, 1, 1-1/4, 1-1/2, 2	
		2 x 2 x 1/2, 3/4, 1, 1-1/4, 1-1/2, 2-1/2	
		2-1/2 x 2-1/2 x 3/4, 1, 1-1/4, 1-1/2, 2, 3	
241	Hex Bushing	1, 1-1/4, 1-1/2, 2,	500
		1-1/4x3/4	
220	Straight Coupling w/stop	1/2, 3/4,	500
		1, 1-1/4, 1-1/2, 2, 2-1/2	
240	Reducing	1 x 1/2, 3/4	500
	Coupling w/hex	1-1/4 x 3/4, 1	
		1-1/2 x 1, 1-1/4	
		2 x 1, 1-1/4, 1-1/2	
180	Cross	1, 1-1/4, 1-1/2, 2	500
		3/4	
180R	Reducing Cross	1-1/4 x 1	500
		1-1/2 x 1	
		2 x 1	
300	Cap	1/2, 3/4, 1,	500
		1-1/4, 1-1/2, 2, 2-1/2	
291	Square Head Plug	1/2, 3/4,	500
		1, 1-1/4, 1-1/2, 2	
342	Union	1, 1-1/4, 1-1/2, 2	500

**CAST IRON FITTINGS**

**Cast Iron Fittings (ANSI/ASME B16.4)**

Model	Configuration	Size, in.	Rated Pressure, psig
90	90° Elbow	1, 1-1/4, 1-1/2, 2, 2-1/2,	300
		3, 4	
90R	Reducing 90° Elbow	3/4 x 1/2	300
		1 x 1/2, 3/4	
		1-1/4 x 1/2, 3/4, 1	
		1-1/2 x 1/2, 3/4, 1, 1-1/4	
		2 x 1/2, 3/4, 1, 1-1/4, 1-1/2	

		2-1/2 x 3/4, 1, 1-1/4, 1-1/2, 2	
		3 x 2	
		3/4x1/2, 3x2	
120	45° Elbow	1, 1-1/4, 1-1/2, 2,	300
		2-1/2, 3, 4	
130	Tee	1, 1-1/4, 1-1/2, 2, 2-1/2	300
		3, 4	
130R	Reducing Tee	1x1x1-1/2, 2x1/2x2, 2x1x1-1/2, 2-1/2x1/2x2-1/2, 2-1/2x2x1/2, 2-1/2x2x3/4, 2-1/2x2x1, 2-1/2x2x1-1/4, 2-1/2x2x1-1/2, 2-1/2x2x2, 2-1/2x2x2-1/2, 3x3x1-1/4, 3x3x1-1/2, 3x3x2	300
180	Cross	1, 1-1/4, 1-1/2, 2	300
180R	Reducing Cross	1-1/4 x 1	300
		1-1/2 x 1	
		2 x 1	
240	Reducing Coupling w/hex	1 x 1/2, 3/4	300
		1-1/4 x 1	
		2 x 3/4, 1	
291	Cored Plugs	3/4, 1, 1-1/4, 1-1/2, 2	300
291S	Solid Plugs	1/2	300

**Malleable Iron Fittings (ANSI/ASME B16.3, ANSI/ASME B16.14)**

**Fittings fabricated with dimensional specifications in accordance with ANSI/ASME B16.3**

Model	Configuration	Size, in.	Rated Pressure, psig
90	90° Elbow	1/2, 3/4, 1, 1-1/4, 1-1/2, 2	500
90	90° Elbow	2-1/2, 3, 3-1/2, 4, 5, 6	300
90R	90° Reducing Elbow	1/2x1/4, 3/8; 3/4x1/4, 3/8, 1/2; 1x3/8, 1/2, 3/4; 1-1/4x1/2, 3/4, 1; 1-1/2x3/4, 1, 1-1/4; 2x3/4, 1, 1-1/4, 1-1/2	500
90R	90° Reducing Elbow	2-1/2x1-1/2, 2; 3x2, 2-1/2; 4x3	300
92	90° Street Elbow	1/2, 3/4, 1, 1-1/4, 1-1/2, 2	500
92	90° Street Elbow	2-1/2, 3, 4, 6	300
120	45° Elbow	1/2, 3/4, 1, 1-1/4, 1-1/2, 2	500
120	45° Elbow	2-1/2, 3, 4, 5, 6	300
121	45° Street Elbow	1/2, 3/4, 1, 1-1/4, 1-1/2, 2	500
121	45° Street Elbow	2-1/2, 3, 4	300
130	Tee	1/2, 3/4, 1, 1-1/4, 1-1/2, 2	500
130	Tee	2-1/2, 3, 3-1/2, 4, 5, 6	300
130R	Reducing Tee	3/8x3/8x1/2, 1/2x1/4x1/2, 1/2x3/8x1/2, 1/2x1/2x1/4, 1/2x1/2x3/8, 1/2x1/2x3/4, 1/2x1/2x1, 3/4x1/2x1/2, 3/4x1/2x3/4, 3/4x3/4x1/4,	500

		3/4x3/4x3/8, 3/4x3/4x1/2, 3/4x3/4x1, 1x1/2x1/2, 1x1/2x3/4, 1x1/2x1, 1x3/4x1/2, 1x3/4x3/4, 1x3/4x1, 1x1x1/4, 1x1x3/8, 1x1x1/2, 1x1x3/4, 1x1x1-1/4, 1x1x1-1/2, 1x1x2, 1-1/4x1/2x1, 1-1/4x1/2x1-1/4, 1-1/4x3/4x3/4, 1-1/4x3/4x1, 1-1/4x3/4x1-1/4, 1-1/4x1x1/2, 1-1/4x1x3/4, 1-1/4x1x1, 1-1/4x1x1-1/4, 1-1/4x1-1/4x3/8, 1-1/4x1-1/4x1/2, 1-1/4x1-1/4x3/4, 1-1/4x1-1/4x1, 1-1/4x1-1/4x1-1/2, 1-1/4x1-1/4x2, 1-1/2x1/2x1-1/2, 1-1/2x3/4x1-1/2, 1-1/2x1x1, 1-1/2x1x1-1/4, 1-1/2x1x1-1/2, 1-1/2x1-1/4x1/2, 1-1/2x1-1/4x3/4, 1-1/2x1-1/4x1, 1-1/2x1-1/4x1-1/4, 1-1/2x1-1/4x1-1/2, 1-1/2x1-1/2x1/2, 1-1/2x1-1/2x3/4, 1-1/2x1-1/2x1, 1-1/2x1-1/2x1-1/4, 1-1/2x1-1/2x2, 2x1/2x2, 2x3/4x2, 2x1x1-1/2, 2x1x2, 2x1-1/4x1-1/4, 2x1-1/4x1-1/2, 2x1-1/4x2, 2x1-1/2x1, 2x1-1/2x1-1/4, 2x1-1/2x1-1/2, 2x1-1/2x2, 2x2x1/2, 2x2x3/4, 2x2x1, 2x2x1-1/4, 2x2x1-1/2	
130R	Reducing Tee	2x2x2-1/2, 2-1/2x1-1/2x2, 2-1/2x1-1/2x2-1/2, 2-1/2x2x2, 2-1/2x2x2-1/2, 2-1/2x2-1/2x3/4, 2-1/2x2-1/2x1, 2-1/2x2-1/2x1-1/4, 2-1/2x2-1/2x1-1/2, 2-1/2x2-1/2x2, 3x2x2, 3x2x3, 3x3x3/4, 3x3x1, 3x3x1-1/4, 3x3x1-1/2, 3x3x2, 3x3x2-1/2, 4x4x1-1/2, 4x4x2, 4x4x2-1/2, 4x4x3	300
134	Street Tee	1/2, 3/4, 1, 1-1/4, 1-1/2, 2	500
165	45° Y-Branches	1/2, 3/4, 1, 1-1/4, 1-1/2, 2	500
165	45° Y-Branches	2-1/2, 3, 4	300
180	Cross	1/2, 3/4, 1, 1-1/4, 1-1/2, 2	500
180	Cross	2-1/2, 3, 3-1/2, 4	300
180R	Reducing Cross	3/4x1/2, 1x1/2, 1x3/4, 1-1/4x3/4, 1-1/4x1, 1-1/2x3/4, 1-1/2x1, 1-1/2x1-1/4, 2x3/4, 2x1, 2x1-1/4, 2x1-1/2	500
180R	Reducing Cross	2-1/2x2, 3x2	300
220	Coupling	1/2, 3/4, 1, 1-1/4, 1-1/2, 2	500
220	Coupling	2-1/2, 3, 4	300
240	Reducing Coupling	1/2x1/8, 1/2x1/4, 1/2x3/8, 3/4x1/4, 3/4x3/8, 3/4x1/2, 1x1/4, 1x3/8, 1x1/2, 1x3/4, 1-1/4x1/2, 1-1/4x3/4, 1-1/4x1, 1-1/2x1/2, 1-1/2x3/4, 1-1/2x1, 1-1/2x1-1/4, 2x1/2, 2x3/4, 2x1, 2x1-1/4, 2x1-1/2	500
240	Reducing Coupling	2-1/2x1-1/2, 2-1/2x2, 3x1-1/2, 3x2, 3x2-1/2, 4x2, 4x3	300
300	Cap	1/2, 3/4, 1, 1-1/4, 1-1/2, 2	500
300	Cap	2-1/2, 3, 3-1/2, 4, 5, 6	300

**Fittings fabricated with dimensional specifications in accordance with ANSI/ASME B16.14**

Model	Configuration	Size, in.	Rated Pressure, psig
241	Bushing	1/2x1/8, 1/2x1/4, 1/2x3/8, 3/4x1/8, 3/4x1/4, 3/4x3/8, 3/4x1/2, 1x1/8, 1x1/4, 1x3/8, 1x1/2, 1x3/4, 1-1/4x1/4, 1-1/4x3/8, 1-1/4x1/2, 1-1/4x3/4, 1-1/4x1, 1-1/2x1/4, 1-1/2x3/8, 1-1/2x1/2, 1-1/2x3/4, 1-1/2x1, 1-1/2x1-1/4, 2x1/4, 2x3/8, 2x1/2, 2x3/4, 2x1, 2x1-1/4, 2x1-1/2, 2-1/2x1/2, 2-1/2x3/4, 2-1/2x1, 2-1/2x1-1/4, 2-1/2x1-1/2, 2-1/2x2, 3x1/2, 3x3/4, 3x1, 3x1-1/4, 3x1-1/2, 3x2, 3x2-1/2, 3-1/2x2-1/2, 3-1/2x3, 4x1-1/4, 4x1-1/2, 4x3, 4x3-1/2, 5x4, 6x5	300
291	Cored Plugs	1/2, 3/4, 1, 1-1/4, 1-1/2, 2, 2-1/2, 3, 3-1/2	300
291S	Solid Plugs	1/2, 3/4, 1, 1-1/4, 1-1/2, 2, 2-1/2, 3, 3-1/2	300
291-4	Slotted Head Plugs	4, 5, 6	300
291N	Countersunk Plugs	1/2, 3/4, 1, 1-1/4, 1-1/2, 2, 2-1/2, 3, 4	300

Malleable Iron Fittings, ISO 49/EN 10242 (threads manufactured in accordance with ISO 7-1):

Fitting Type	Sizes, in.	End Type	Rated Pressure, psig
Bend 90 degree, male and female	1/8", 1/4", 3/8", 1/2", 3/4", 1", 1-1/4", 1-1/2", 2", 2-1/2", 3", 4", 6"	Threaded	500
Short Bend 90 degree, male and female	1/4", 3/8", 1/2", 3/4", 1", 1-1/4", 1-1/2", 2", 2-1/2"	Threaded	500
Bend 90 degree, female	1/4", 3/8", 1/2", 3/4", 1", 1-1/4", 1-1/2", 2", 2-1/2", 3", 4"	Threaded	500
Short Bend 90 degree, female	1/2", 3/4", 1", 1-1/4", 1-1/2", 2"	Threaded	500
Bend 90 degree, male	3/8", 1/2", 3/4", 1", 1-1/4", 1-1/2", 2", 2-1/2", 3", 4"	Threaded	500
Bend 45 degree, male and female	1/4", 3/8", 1/2", 3/4", 1", 1-1/4", 1-1/2", 2", 2-1/2", 3", 4", 6"	Threaded	500
Bend 45 degree, female	1/4", 3/8", 1/2", 3/4", 1", 1-1/4", 1-1/2", 2", 2-1/2", 3", 4"	Threaded	500
Crossover	1/2", 3/4", 1", 1-1/4", 1-1/2", 2"	Threaded	500
Elbow, 90 degree	1/8", 1/4", 3/8", 1/2", 3/4", 1", 1-1/4", 1-1/2", 2", 2-1/2", 3", 4", 6", 5"	Threaded	500
Elbow, 90 degree, reducing	3/8"x1/4", 1/2x3/8", 3/4x3/8", 3/4x1/2", 1x1/2", 1x3/4", 1-1/4x3/4", 1-1/4x1", 1x1/4", 1x3/8", 1x1/2", 1x3/4", 1-1/4x3/8", 1-1/4x1/2", 1-1/4x3/4", 1-1/4x1", 1-1/2x1/2", 1-1/2x3/4", 1/4x1/8, 3/8x1/8, 1/2x1/4, 3/4x1/4, 1x1/4, 1x3/8, 1-1/4x3/8, 1-1/4x1/2, 1-1/2x1/2, 1-1/2x3/4, 2x1/2, 2x3/4, 2x1, 2x1-1/4, 2-1/2x1/2, 2-1/2x3/4, 2-1/2x1, 2-1/2x1-1/4, 2-1/2x1-1/2, 3x3/4, 3x1, 3x1-1/4, 3x1-1/2, 3x2, 3x2-1/2, 4x1, 4x1-1/4, 4x1-1/2, 4x2, 4x2-1/2, 4x3, 6x4	Threaded	500
	11/2x1", 11/2x11/4", 2x11/2", 21/2x2"		
Stree Elbow, 90 degree	1/8", 1/4", 3/8", 1/2", 3/4", 1", 1-1/4", 1-1/2", 2", 2-1/2", 3", 4", 6"	Threaded	500
Stree Elbow, 90 degree, reducing	3/4"x1/2", 1"x3/4"	Threaded	500
Union elbow, F&F, Flat seat without gasket	1/2", 3/4, 1, 1-1/4, 1-1/2, 2"	Threaded	500
Union elbow, F&F, conical joint iron to iron	1/4, 3/8, 1/2", 3/4, 1, 1-1/4, 1-1/2, 2"	Threaded	500
Union elbow, M&F, Flat seat without gasket	1 1/2"	Threaded	500
Union elbow, M&F, conical joint iron to iron	1/2", 3/4, 1, 1-1/4, 1-1/2, 2"	Threaded	500
Elbow, 45 degree	1/8", 1/4", 3/8", 1/2", 3/4", 1", 1-1/4", 1-1/2", 2", 2-1/2", 3", 4", 5, 6"	Threaded	500
Stree Elbow, 45 degree	1/8", 1/4", 3/8", 1/2", 3/4", 1", 1-1/4",	Threaded	500
	1-1/2", 2, 2-1/2, 3, 4"		
Tee	1/8", 1/4", 3/8", 1/2", 3/4", 1", 1-1/4", 1-1/2", 2", 2-1/2", 3", 4", 5, 6"	Threaded	500
Tee, reducing	3/8x1/4, 1/2x1/4, 1/2x3/8, 3/4x1/4,	Threaded	500
	3/4x3/8, 3/4x1/2, 1x1/4, 1x3/8, 1x1/2, 1x3/4, 1-1/4x3/8, 1-1/4x1/2,		
	1-1/4x3/4, 1-1/4x1, 1-1/2x1/2, 1-1/2x3/4, 1-1/2x1, 1-1/2x1-		

	1/4, 2x1/2, 2x3/4, 2x1,		
	2x1-1/4, 2x1-1/2, 2-1/2x1, 2-1/2x1-1/4, 2-1/2x1-1/2, 2-1/2x2, 3x1, 3x1-1/4, 3x1-1/2, 3x2, 3x2-1/2, 4x2, 4x3, 1/4x1/8, 1/2x1/8, 1-1/2x3/8, 2x3/8, 2-1/2x1/2, 2-1/2x3/4, 3x1/2, 3x3/4, 4x1/2, 4x3/4, 4x1, 4x1-1/4, 4x1-1/2, 4x2-1/2, 6x2, 6x3, 6x4, 1/2x1/2x3/4, 1/2x1/2x1, 3/4x3/4x1,		
	3/4x3/4x1-1/4, 1x1x1-1/4, 1x1x1-1/2, 1x1x2, 1x1x2-1/2, 1-1/4x1-1/4x1-1/2, 1-1/4x1-1/4x2, 1-1/2x1-1/2x2, 1-1/2x1-1/2x2-1/2, 2x2x2-1/2, 2-1/2x2-1/2x3, 2-1/2x2-1/2x4, 3/4x1/2x1/2, 1x1/2x1/2, 1x3/4x3/4,		
	1-1/4x1/2x1/2, 1-1/4x3/4x3/4, 1-1/4x1x1, 1-1/2x3/4x3/4, 1-1/2x1x1, 1-1/2x1-1/4x1-1/4, 2x1x1, 2x1-1/4x1-1/4, 2x1-1/2x1-1/2, 2-1/2x2x2, 3x2x2, 3/4x1/2x3/4, 1x1/2x1, 1x3/4x1, 1x1/4x1, 1-1/4x1/2x1-1/4, 1-1/4x3/4x1-1/4, 1-1/4x1x1-1/4, 1-1/2x1/2x1-1/2, 1-1/2x3/4x1-1/2, 1-1/2x1x1-1/2, 1-1/2x1-1/4x1-1/2, 2x1/2x2, 2x3/4x2, 2x1x2,		
	2x1-1/4x2, 2x1-1/2x2, 2-1/2x1-1/2x2-1/2, 2-1/2x2x2-1/2, 3/4x1/2x1, 1x1/2x3/4, 1x3/4x1/2,	Threaded	500
	1-1/4x1/2x3/4, 1-1/4x1/2x1, 1-1/4x3/4x1/2, 1-1/4x3/4x1, 1-1/4x1x1/2, 1-1/4x1x3/4, 1-1/2x3/4x1, 1-1/2x3/4x1-1/4, 1-1/2x1x1/2, 1-1/2x1x1-1/4, 1-1/2x1-1/4x1/2, 1-1/2x1-1/4x3/4, 1-1/2x1-1/4x1,		
	1-1/2x1-1/4x2, 2x1x1-1/2, 2x1-1/4x1, 2x1-1/4x1-1/2, 2x1-1/2x1/2, 2x1-1/2x3/4, 2x1-1/2x1, 2x1-1/2x1-1/4, 2-1/2x2x1/2, 2-1/2x2x1, 2-1/2x2x1-1/4		
Pitcher Tee, equal 90 degree	1/2, 3/4, 1, 1-1/4, 1-1/2, 2"	Threaded	500
Service Tee, equal	1/4", 1/2, 3/4, 1, 1-1/4, 1-1/2, 2"	Threaded	500
Service Tee, Reducing	2"X1 1/2", 2-1/2x2, 3X2 1/2"	Threaded	500
Lateral Y branch, 45 degree	1/2", 3/4", 1", 1-1/4", 1-1/2", 2", 2-1/2", 3", 4	Threaded	500
Cross	1/8", 1/4, 1/2", 3/4", 1", 1-1/4", 1-1/2", 2", 2-1/2", 3", 4", 3/8"	Threaded	500
Cross, reducing	3/4"X1 1/2", 1x1/2, 1x3/4, 1-1/4x3/4, 1-1/4x1, 1 1/2"X1", 1 1/4"X1 1/2", 1-1/2x1/2, 1-1/2x3/4, 1-1/2x1-1/4, 2x3/4, 2x1, 2x1-1/4, 2x1-1/2, 2 1/2"X1", 2 1/2"X1 1/4", 2 1/2"X1 1/2", 2 1/2"X2", 3x3/4, 3x1, 3x1-1/4, 3x1-1/2, 3"X2", 3"X2 1/2", 4x1, 4x1-1/4, 4x1-1/2, 4x2, 4x2-1/2, 4"X3"	Threaded	500
Socket/Coupling	1/8", 1/4", 3/8", 1/2", 3/4", 1", 1-1/4", 1-1/2", 2", 2-1/2", 3", 4", 5, 6"	Threaded	500
Socket/Coupling, reducing	1/4"X1/8", 3/8x1/8, 3/8x1/4, 1/2x1/4, 1/2x3/8, 3/4x1/4, 3/4x3/8, 3/4x1/2, 1x3/8, 1x1/2, 1"X3/4, 1 1/4"X1/2, 1-1/4x3/4, 1-1/4x1, 1-1/2x1/2, 1-1/2x3/4, 1-1/2x1, 1-1/2x1-1/4, 2x1/2, 2x3/4, 2x1, 2x1-1/4, 2"X1 1/2", 2 1/2"X1 1/4", 2 1/2"X1 1/2, 2 1/2"X2, 3x1-1/2, 3x2, 3"X2 1/2", 1/2"X1/8", 3/4"X1/8", 1x1/4, 1-1/4x1/4, 1-1/4x3/8, 1-1/2x1/4, 1-1/2x3/8, 2-1/2x1/2,	Threaded	500

	2-1/2x3/4, 2-1/2x1, 3x1/2, 3x3/4, 3x1, 3"x11/4"		
Bushing(241)	1/4"x1/8", 3/8x1/8, 3/8x1/4, 1/2x1/8,	Threaded	500
	1/2x1/4, 1/2x3/8, 3/4x1/8, 3/4x1/4, 3/4x3/8, 3/4x1/2, 1x1/8, 1x1/4, 1"x3/8", 1x1/2, 1x3/4, 1-1/4x1/4, 1-1/4x3/8, 1-1/4x1/2, 1-1/4x3/4, 1-1/4x1, 1-1/2"x1/4", 1-1/2"x3/8", 1-1/2"x1/2", 21/2"x11/2", 2-1/2x2, 3x1/2, 3x3/4, 3x2, 3"x21/2", 11/2"x3/4", 1-1/2x1, 1-1/2x1-1/4, 2x1/4, 2x3/8, 2x1, 2x1-1/4, 2x1-1/2, 2-1/2x1/2, 21/2"x3/4", 31/2"x3", 4x3/4, 4x1, 4x1-1/4, 4x1-1/2, 4x3, 5x3, 5x4, 6x2, 6x2-1/2, 6x5		
Bushing(241D)	2"x1/2", 2x3/4, 2-1/2x1, 2-1/2x1-1/4, 3x1, 3x1-1/4, 3x1-1/2, 4x2, 4x2-1/2, 6x3, 6x4	Threaded	500
Hexagon Nipple, reducing	3/8"x1/4", 1/2x1/4, 1/2x3/8, 3/4x3/8, 3/4x1/2, 1x1/2, 1x3/4, 1-1/4x1/2, 1-1/4x3/4, 11/4"x1", 11/2"x3/4", 1-1/2x1, 1-1/2x1-1/4, 2x1, 2x1-1/4, 2x1-1/2, 2-1/2x2, 3x2, 3"x21/2", 1/4"x1/8", 3/4x1/4, 1-1/2x1/2, 2x1/2, 2x3/4, 2-1/2x1, 2-1/2x1-1/4, 2-1/2x1-1/2, 3x1-1/2, 4x2, 4x2-1/2, 4"x3"	Threaded	500
Extension piece, sockets M&F, reducing	3/8"x1/4", 1/2x1/4, 1/2x3/8, 3/4x3/8, 3/4x1/2, 1x1/2, 1x3/4, 1-1/4x1/2, 1-1/4x3/4, 1-1/4x1, 1-1/2x3/4, 1-1/2x1, 1-1/2x1-1/4, 2x1, 2x1-1/4, 2"x11/2"	Threaded	500
Socket, parallel threads, equal	1/8", 1/4", 3/8", 1/2", 3/4", 1", 1-1/4", 1-1/2", 2", 2-1/2", 3", 4", 6"	Threaded	500
Socket, right & left threads	1/2", 3/4", 1, 1-1/4, 1-1/2, 2"	Threaded	500
Hexagon Nipple, equal	1/8", 1/4", 3/8", 1/2", 3/4", 1", 1-1/4", 1-1/2", 2", 2-1/2", 3", 4", 5", 6"	Threaded	500
Plug	1/8", 1/4", 3/8", 1/2", 3/4", 1", 1-1/4", 1-1/2", 2", 2-1/2", 3", 4", 6"	Threaded	500
Countersunk Plug	1/2, 3/4", 1", 1-1/4", 1-1/2", 2", 2-1/2", 3"	Threaded	500
Solid Plug	1/4", 3/8", 1/2", 3/4", 1", 1-1/4",	Threaded	500

	1-1/2", 2", 2-1/2", 3", 4"		
Cap	1/8", 1/4", 3/8", 1/2", 3/4", 1", 1-1/4",	Threaded	500
	1-1/2", 2", 2-1/2", 3", 4", 5, 6"		
Locknut	1/4", 3/8", 1/2", 3/4", 1", 1-1/4",	Threaded	500
	1-1/2", 2", 2-1/2", 3", 4"		
Backnut	1/2", 3/4", 1", 1-1/4",	Threaded	500
	1-1/2", 2", 4"		
Flange(321-4)	1-1/4",	Threaded	500
	1-1/2", 2", 2-1/2", 3", 4", 6"		
Flange(321-6)	1-1/4",	Threaded	500
	1-1/2", 2", 2-1/2", 3", 4", 6"		
Flange(321H)	1/2", 3/4", 1", 1-1/4",	Threaded	500
	1-1/2", 2", 2-1/2", 3", 4"		
Flange(321N)	2"	Threaded	500
Flange, DRP D	1/2", 3/4", 1", 1-1/4",	Threaded	500
	1-1/2", 2", 2-1/2", 3", 4", 5, 6"		
Flange, U/D	1/2", 3/4", 1", 1-1/4",	Threaded	500
	1-1/2", 2", 2-1/2", 3", 4", 5, 6"		
Flange, BS Table D	1", 1-1/4",	Threaded	500
	1-1/2", 2", 2-1/2", 3", 4", 6"		
Flange, without bolt hole	1/2", 3/4", 1", 1-1/4",	Threaded	500
	1-1/2", 2", 2-1/2", 3", 4"		
Extension Tube	1/2"X30, 1/2"X40, 1/2"X50, 1/2"X60,	Threaded	500
	1/2"X100		
Extention Long piece	1/2", 3/4", 1", 1-1/4",	Threaded	500
	1-1/2", 2"		
Extention Short piece	1/2"	Threaded	500
Elbow, 90 degree, plain	1/2", 1-1/4", 2"	Threaded	500
Tee, plain	1/2", 1", 1-1/4",	Threaded	500
	1-1/2"		
Socket, plain, with ribs	1/2", 3/4", 1", 1-1/4",	Threaded	500
	1-1/2", 2", 2-1/2", 3"		
Side outlet elbow	1/2", 3/4", 1", 1-1/4",	Threaded	500
	1-1/2", 2"		
Side outlet tee	1/2", 3/4", 1"	Threaded	500

Steel Fittings, EN 10241 (threads manufactured in accordance with DIN 2999):



Fitting Type	Sizes, in.	End Type	Rated Pressure, psig
Steel Merchant Couplings/Sockets	1/8", 1/4", 3/8", 1/2", 3/4", 1", 1-1/4", 1-1/2", 2", 2-1/2", 3", 4", 5", 6"	Threaded	500
Half Steel Merchant Couplings/Sockets	1/8", 1/4", 3/8", 1/2", 3/4", 1", 1-1/4", 1-1/2", 2", 2-1/2", 3", 4", 5", 6"	Threaded	500
Steel Merchant Couplings/Sockets/Half	1/8", 1/4", 3/8", 1/2", 3/4", 1", 1-1/4", 1-1/2", 2", 2-1/2", 3", 4", 5", 6"	Threaded	500

Steel Fittings, ASTM A865 (threads manufactured in accordance with ANSI B1.20.1):

Fitting Type	Sizes, in.	End Type	Rated Pressure, psig
Steel Merchant Couplings/Sockets	1/8", 1/4", 3/8", 1/2", 3/4", 1", 1-1/4", 1-1/2", 2", 2-1/2", 3", 4", 5", 6"	Threaded	500

Steel Fittings, BS1387(threads manufactured in accordance with ISO 7-1):

Fitting Type	Sizes, in.	End Type	Rated Pressure, psig
Steel Merchant Couplings/Sockets	1/4", 3/8", 1/2", 3/4", 1", 1-1/4", 1-1/2", 2", 2-1/2", 3", 4", 5", 6"	Threaded	500

Last Updated on 2011-03-14

[Questions?](#)

[Print this page](#)

[Notice of Disclaimer](#)

[Page Top](#)

Copyright © 2011 Underwriters Laboratories Inc.®

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Listed and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Designs and/or Listings (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from Underwriters Laboratories Inc." must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "Copyright © 2011 Underwriters Laboratories Inc.®"

An independent organization working for a safer world with integrity, precision and knowledge.

